

# Test Certificate



Ref No : TC260361  
Customer : Industrial Engineering Equipments  
PO No: : 2627010POIEE  
Model : SE 1 PFO H10 A3 S6 0  
Serial No. : A25081335 TO A25081359


Ref Date : 21/05/2026  
PO Date : 14/05/2026  
Quantity : 25

## SPECIFICATIONS

Switch Type : Pressure Switch Fixed Differential  
Range : 0.5 - 10.0 bar , (7.25 - 145.037) (psi)  
On Off Differential : 1.0 bar (Approximate Max) , (14.50) (psi)  
Max Pressure/Temp : 35 bar , (507.5) (psi)  
Micro Switch : 5A, 250VAC; 0.2A, 250 VDC (res.)  
Pressure Port : SS316L / M10x1 M  
Diaphragm : Nitrile  
Enclosure : Aluminium  
Repeatability : +/- 2% FSR  
Operating Type : With Silver Contact SPDT  
Terminal Type : Plug Type

Temp.of Working Medium : 80° C Max for Neoprene or Teflon diaphragm 150° C Max for SS 316L or  
Other Metallic sensing elements. For higher temperatures, please use an appropriate length of impulse tube.

The items mentioned here in have been tested & confirmed to the above specifications.

  
For Kaustubh Udyog  
( Q.A.)